

# Aluminium 19" rack cases

Front and rear lids with latches and IP65 seals

Spring loaded handles

19" inner frame for fitting equipment

Isolating anti vibration mount between frame and housing

## Key Features

- Lightweight aluminium construction •
- Access lids front and rear •
- 19" Shock mounted frame •
- Sealed to IP65 •
- Automatic pressure relief valve - PRV •
- Range of options •



Aerospace



Airforce



Retail



Photographic



Scientific



Medical



Security



Electronics



Engineering



Naval



Custom



Military

# Aluminium 19" rack cases

Aluminium enclosures with front and rear access lids, fitted with 19" shock mounted frames to give protection from mechanical stresses including shock, impact and vibrations.

Standard frame depths are 480mm and 610mm, but many others can be supplied as required.

U Size	Internal Dimensions of Frame (mm)		
	Height	Width	Depth
3U	134	450	480
3U	134	450	610
4U	178	450	480
4U	178	450	610
5U	223	450	480
5U	223	450	610
6U	267	450	480
6U	267	450	610
7U	312	450	480
7U	312	450	610
8U	356	450	480
8U	356	450	610
9U	401	450	480
9U	401	450	610
10U	445	450	480
10U	445	450	610
11U	490	450	480
11U	490	450	610
12U	534	450	480
12U	534	450	610

